

## ZNR™ RA

### Printed Concrete Mold Release Agent

<b>Product Description</b>	Colored mold release agent that contributes vintage appearance to the surface in cement-based printed concrete applications.														
<b>Product Number</b>	611														
<b>Areas of Application</b>	All printed concrete hardener applications.														
<b>Characteristics /Advantages</b>	<ul style="list-style-type: none"> <li>Prevents adhesion of concrete surface hardeners to molds.</li> <li>Prevents abrasion of molds.</li> <li>Vintage, desired color and decorative.</li> <li>Provides transmission of mold patterns to the surface properly.</li> </ul>														
<b>Technical Data</b>	<table border="1"> <tr> <td>Color</td><td>Grey and special desired colors</td></tr> <tr> <td>Appearance</td><td>Micronized powder</td></tr> <tr> <td>Package</td><td>5 kg plastic bucket</td></tr> <tr> <td>Consumption</td><td>Approximately 0.200–0.300 kg/m<sup>2</sup></td></tr> <tr> <td>Cleaning of tools</td><td>With water</td></tr> <tr> <td>Storage</td><td>Shelf life is approximately 12 months in a cool and dry environment.</td></tr> <tr> <td>Danger class</td><td>Non-flammable. Do not inhale or avoid eye contact because the product is micronized powder.</td></tr> </table>	Color	Grey and special desired colors	Appearance	Micronized powder	Package	5 kg plastic bucket	Consumption	Approximately 0.200–0.300 kg/m <sup>2</sup>	Cleaning of tools	With water	Storage	Shelf life is approximately 12 months in a cool and dry environment.	Danger class	Non-flammable. Do not inhale or avoid eye contact because the product is micronized powder.
Color	Grey and special desired colors														
Appearance	Micronized powder														
Package	5 kg plastic bucket														
Consumption	Approximately 0.200–0.300 kg/m <sup>2</sup>														
Cleaning of tools	With water														
Storage	Shelf life is approximately 12 months in a cool and dry environment.														
Danger class	Non-flammable. Do not inhale or avoid eye contact because the product is micronized powder.														
<b>Preparation Instructions</b>	The product is ready for use.														
<b>Application</b>	Immediately after <b>ZNR Printed Concrete YS</b> application, sprinkle <b>ZNR RA</b> on the surface and proceed with printing with molds. Wash the surface with pressurized water a few days after application until the desired effect is obtained. While washing with high pressure leaves a less vintage effect, washing with low pressure leaves more vintage effect.														
<b>General Matters</b>	Abovementioned product data and descriptions are prepared for guiding purposes as a result of our experiences and diligent studies. We, individually, can not control or affect the variety of the related materials and various construction and working conditions. Warranty is limited to only quality of the purchased material for the applications that are not under our control. No warranty is committed for application, but only for product manufacturing. This technical flyer overrides former flyers. Quality of the work may vary depending on how professionally the product is used. In case of hesitation, please perform a small test or ask for technical help.														
<b>Disposal</b>	Empty packings can be disposed to collection bins according to regional/local regulations or recycling rules. Dispose used waste materials as construction waste materials after drying and hardening. It is dangerous to dispose by burning the product remnants.														
<b>Safety Information</b>	Keep the products out of reach of children. Keep the lids of the products closed. It is recommended to use gloves and goggles during application. In case of contact with skin, wash immediately with soap. In case of contact with eyes, immediately consult a doctor. For more information, please refer to the material safety data sheet.														