

ZNR™ P 300
Adherence Enhancer Impermeable Surface Primer

Product Description	Polymer dispersion based and mineral-filled, one-component, adherence enhancer primer with reinforced adherence characteristic that can be used on impermeable surfaces.																				
Product Number	203																				
Areas of Application	<ul style="list-style-type: none"> • Ceramic, • Exposed concrete, • Sandstone, marble, clinker, • Smooth and glossy surfaces such as plywood • Absorbent surfaces such as gypsum, concrete, plaster screed, wood, etc. 																				
Characteristics /Advantages	<ul style="list-style-type: none"> • Economic. • Easy-to-use. It can be applied using brush or roller. • Enhances adhesion strength by forming a rough surface for adhesion of tiles on smooth and glossy surfaces. • Provides insulation by settling into pores. • Provides clinging of the chalking on the surface and thus enhances adherence of tiles on the surface. • Solvent-free. Environment and human health friendly. 																				
Technical Data	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>Package</td><td>3 kg or 5 kg plastic buckets</td></tr> <tr> <td>Appearance</td><td>Light pink liquid</td></tr> <tr> <td>Density</td><td>~1.15 gr/cm³</td></tr> <tr> <td>Viscosity</td><td>70 – 80 KU (~1200 mPa.s)</td></tr> <tr> <td>Application surface temperature</td><td>+5°C / +35 °C</td></tr> <tr> <td>Full-Dry Time</td><td>60 minutes (variable, depending on ambient conditions)</td></tr> <tr> <td>Waiting time</td><td>Max. 48 hours</td></tr> <tr> <td>Consumption</td><td>0,150-0,250 kg/m² (variable, depending on surface conditions)</td></tr> <tr> <td>Application tools</td><td>Roller or Brush</td></tr> <tr> <td>Storage</td><td>Shelf life is approximately 12 months in a cool and dry environment.</td></tr> </table>	Package	3 kg or 5 kg plastic buckets	Appearance	Light pink liquid	Density	~1.15 gr/cm ³	Viscosity	70 – 80 KU (~1200 mPa.s)	Application surface temperature	+5°C / +35 °C	Full-Dry Time	60 minutes (variable, depending on ambient conditions)	Waiting time	Max. 48 hours	Consumption	0,150-0,250 kg/m ² (variable, depending on surface conditions)	Application tools	Roller or Brush	Storage	Shelf life is approximately 12 months in a cool and dry environment.
Package	3 kg or 5 kg plastic buckets																				
Appearance	Light pink liquid																				
Density	~1.15 gr/cm ³																				
Viscosity	70 – 80 KU (~1200 mPa.s)																				
Application surface temperature	+5°C / +35 °C																				
Full-Dry Time	60 minutes (variable, depending on ambient conditions)																				
Waiting time	Max. 48 hours																				
Consumption	0,150-0,250 kg/m ² (variable, depending on surface conditions)																				
Application tools	Roller or Brush																				
Storage	Shelf life is approximately 12 months in a cool and dry environment.																				
Surface Preparation	Remove loose parts, grease and other chemicals from the application area.																				
Preparation Instructions	ZNR P 300 is ready for use . Mix well before use. Do not add any additives.																				
Application	Apply ZNR P 300 on the surface equally using a roller or brush and let it dry. Apply 2 layers on highly absorbent surfaces such as gypsum, screed or concrete. Dry time is approximately 60 minutes. Drying time may vary depending on the weather conditions and surface status. Do not proceed with application on it before drying. It is recommended to apply another layer if waiting time exceeds 48 hours.																				
Considerations	<ul style="list-style-type: none"> • Application area of ZNR P 300 should be protected from water contact. • Temperature of the application area should be minimum +5 °C. • Wash your hands and application tools with plenty of water after application. 																				
General Matters	Abovementioned product data and descriptions are prepared for guiding purposes as a result of our experiences and diligent studies. We, individually, can not control or affect the variety of the related materials and various construction and working conditions. Warranty is limited to only quality of the purchased material for the applications that are not under our control. No warranty is committed for application, but only for product manufacturing. This technical flyer overrides former flyers. Quality of the work may vary depending on how professionally the product is used. In case of hesitation, please perform a small test or ask for technical help.																				
Disposal	Empty packings can be disposed to collection bins according to regional/local regulations or recycling rules. Dispose used waste materials as construction waste materials after drying and hardening. It is dangerous to dispose by burning the product remnants.																				
Safety Information	Keep the products out of reach of children. Keep the lids of the products closed. It is recommended to use gloves and goggles during application. In case of contact with skin, wash immediately with soap. In case of contact with eyes, immediately consult a doctor. For more information, please refer to the material safety data sheet.																				